

WHEELERS 2 STROKE - VS

Synthetic High Performance 2-Stroke Oil

Product Description

Wheelers 2 stroke VS is a fully synthetic 2-stroke motor oil to be used in air- and water-cooled road and racing engines. Its capacity exceeds the actually most stringent specification requirements of all 2-stroke motor manufacturers.

Wheelers 2 stroke VS is produced from high-temperature proof and most lubricious synthetic base oils and special low-ash additives of latest technology, which assure

- optimal motor lubrication even under high-speed racing conditions
- reduction of deposits in the combustion chamber, at the sparking plugs, in the circular grooves and the exhaust system.
- Improved pollution control by scentless and smokeless combustion.
- universal use in all lubrication systems (fresh oil lubrication, auto-lube systems, mixed lubrication) and for all gasoline fuels

Wheelers 2 stroke VS was designed for the use in high-speed racing engines of motor cycles and carts as well as for normal sports engines or for 2-stroke engines, which require disproportionately high lubrication guarantee.

Specification

API TC
JASO FD
ISO - L - EGD

Typical Values

Wheelers 2 Stroke VS	Unit	Value	Method
Density at 15	kg/m ³	888	DIN 51 757
Color		green	visual
Viscosity at 40°C	mm ² /s	63,30	DIN 51 562
Viscosity at 100°C	mm ² /s	8,373	DIN 51 562
Viscosity Index		101	DIN ISO 2909
Pourpoint	°C	-39	DIN ISO 3016
Flash Point	°C	98	DIN ISO 2592
TBN	mg KOH/g	0,18	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831