



WHEELERS AGRICULTURE STOU HC

SAE 10W-40

SUPER UNIVERSAL TRACTOR OIL

Description and Properties

Wheeler's AGRICULTURE STOU HC SAE 10W-40 is an all-seasons multigrade oil for the use in all types of agricultural machines

Wheeler's AGRICULTURE STOU HC SAE 10W-40 is used and recommended in agricultural machines because of its multi-functional properties in engines, gears and hydraulics as well as in enclosed brake systems ("wet brakes"). Furthermore this universal oil is outstandingly applicable to provide all machines and aggregates in the agricultural domain

Wheeler's AGRICULTURE STOU HC SAE 10W-40 is produced from selected base oils and innovative additives, and therefore it is optimal tuned to fulfil the multifaceted operation conditions of agricultural machines.

Wheeler's AGRICULTURE STOU HC SAE 10W-40

- provides trouble-free operation for engines, gears, axes, differentials, hydraulic- and brake-systems
- reduces the forming of aging-products at high temperatures
- absorbs acid gases from the fuel combustion
- assures optimally balanced frictional behaviour in wet brakes and clutches
- has a low foaming tendency

Qualification / Recommendation

API CG-4	Ford M2C159B/C, M2C86B/C, M2C134D
ACEA E3 (Niveau)	Allison C-4
API GL-4	Fendt Vario
API GL-5 (für Landmaschinen)	John Deere JDM / J20C / J27
HVLP-D gem. DIN 51 524 Teil 3 (für 10W40)	Massey Ferguson M1135 bis 1145
Case M5 / 1118 / 1207 / 1209 / MAT3525 / CS / CVX	Landini / Lindner / Mc-Cormick
Claas Renault Agriculture	ZF TE-ML-06B (inc.06R), -06C, -07B
Valmet (inkl.stufenlos)	Steyr Serie 900 / 9000 / CVT
New Holland NH 410B / 420A / 526 C	Harvester B6
Same-Deutz-Lamborghini-Hirlimann T3245 / 3340 / 3345 / 3445 / 3450 / 3550	

Typical Properties

Wheeler's AGRICULTURE STOU HC	Unit	Value	Method
Density at 15°C	kg/m ³	866	DIN 51 757
Viscosity at 40°C	mm ² /s	91,9	DIN 51 562
Viscosity at 100°C	mm ² /s	13,90	DIN 51 562
Viscosity Index		155	DIN ISO 2909
dynam. viscos.at -25°C	mPa.s	6320	ASTM D5293
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	226	DIN ISO 2592
TBN	mg KOH/g	10,3	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheeler's GmbH
 Jubiläumsstraße 2
 01139 Dresden / Germany
 Tel. 49 - (0) 351 16056831