

WHEELERS ATF DEX III H Red

AUTOMATIC TRANSMISSION FLUID

Description

WHEELERS ATF DEXRON III H -fluid is an Automatic Transmission Fluid, which is made from mineral base oils and products from the synthesis technology, in combination with a special additive package.

Application

WHEELERS ATF DEXRON III H is used in automatic vehicle gears, servo steering's, fluid couplings and hydrodynamic converters as well as in hydraulics of passenger cars, commercial vehicles, busses and construction vehicles, if an ATF of Dexron III H - type is recommended.

Properties

WHEELERS ATF DEXRON III H affords following benefits:

- Optimally balanced frictional behaviour
- Very good wear protection
- Excellent cold fluidity
- Outstanding oxidation stability
- Good corrosion- and rust preventive properties
- Low foaming tendency and best elastomer compatibility

Specification

DEXRON III H und Dexron III G	Ford Mercon
Allison C-4	Voith 55.6335 & 55.6336
MB 236.1, 236.5, 236.6 & 236.7	ZF TE-ML 02F, 03D, 04D, 09,11B, 14A, 17C
MAN 339 Typ Z1 & V1, Z2 & V2	Cat TO-2
Volvo 97340, 97341	Allison TES, 389
Ford M2C138-CJ, M2C 166-H	

Nominal Values

WHEELERS ATF DEXRON III H	Unit	Value	Method
Density at 15	kg/m ³	851	DIN 51 757
Viscosity at 40°C	mm ² /s	40,00	DIN 51 562
Viscosity at 100°C	mm ² /s	8,10	DIN 51 562
Viscosity Index		182	DIN ISO 2909
Pourpoint	°C	-50	DIN ISO 3016
Flash Point	°C	220	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831