



WHEELERS MOTOR OIL - HCL

SAE 15W-40

High Performance Multigrade Motor Oil for Passenger Cars

Product Description

Wheelers Motor oil HCL SAE 15W40 is a multigrade motor oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality base oils and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged.

Wheelers Motor oil HCL SAE 15W40 by its optimized formulation provides lowered fuel- and oil Consumption. Because of its extended viscosity range the all seasons use is possible. A special booster raises the quality level up to API SN, which provides improved oxidation resistance, improved deposit protection, better wear protection, and better low-temperature performance over the life of the oil. This causes an improved motor cleanliness and at least an extended motor life.

Specification/Recommendation

ACEA A3- / B4-08
API SN / CF
MB 229.1
VW 505 00

Typical Values

Wheelers Motor oil HCL SAE 15W40	Unit	Value	Method
Density at 15	kg/m ³	865	DIN 51 757
Viscosity at 40°C	mm ² /s	108	DIN 51 562
Viscosity at 100°C	mm ² /s	15,7	DIN 51 562
Viscosity Index		156	DIN ISO 2909
CCS at -30°C	mPa.s	6580	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flash Point	°C	220	DIN ISO 2592
TBN	mg KOH/g	8,5	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831