

WHEELERS MOTOR OIL -WHC

SAE 5W-40

Fully Synthetic High Performance Low Friction Oil

Description

Wheelers WHC SAE 5W40 is a high performance low friction oil, which is designed for all gasoline and diesel engines of passenger cars, and which especially can be used for fuel injected and turbo charged engines.

It is blended from high quality synthetic base oils and selected additives. This makes for a lubricant quality which fulfils and exceeds all requirements of modern passenger car engines

Product Benefits

Wheelers WHC SAE 5W40 has following advantages to be pointed out.

- excellent cold start and fast oil feed even at temperatures down to lower than -30°C assure fuel- and oil-economy.
- optimized high temperature viscosity to meet latest requirements leads to low oil-caused emissions.
- high wear and corrosion protection and a very good dispersancy provide for an excellent cleanliness of the engine and for long motor life.
- All seasons use by outstanding temperature-viscosity properties and reliable performance reserves even at long drain intervals

Specification / Approvals

ACEA A3- / B4-12
 API SN / CF
 Renault RN 710/700
 Porsche A40
 Opel GM-LL-B-025
 PSA B71 2296

VW 502 00 / 505 00
 MB-Approval 229.3

Typical Values

Wheelers WHC SAE 5W40	Unit	Value	Method
Density at 15	kg/m ³	859	DIN 51 757
Viscosity at 40°C	mm ² /s	82,6	DIN 51 562
Viscosity at 100°C	mm ² /s	13,60	DIN 51 562
Viscosity Index		169	DIN ISO 2909
CCS at -30°C	mPa.s	6750	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flash Point	°C	228	DIN ISO 2592
TBN	mg KOH/g	7,7	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH
 Jubiläumsstraße 2
 01139 Dresden / Germany
 Tel. 49 - (0) 351 16056831