

WHEELERS MOTOR OIL- VOS SAE 0W-20

Fully Synthetic High Performance Low Friction Motor Oil, special designed for VW vehicles.

 \mathbf{P} roduct \mathbf{D} escription

WHEELERS VOS SAE 0W-20 is a fully synthetic low friction oil to be used in passenger cars gasoline and diesel engines. The special formulation assures maximum thermal and mechanical stability, excellent viscosity temperature dependency and low evaporation loss. The low friction properties of the used synthetic base stocks provide in conjunction with the most modern antifriction additives noticeable reduction of fuel consumption and thus for protection of environment by decreasing pollution.

WHEELERS VOS SAE 0W-20 grants maximum wear protection and features best low temperature properties. These assure fast oil provision at all lubrication areas and minimize cold starting wear. Highly effective dispersant additives prevent sludge built-up in the oil circuit and deposits on piston and inlets valves. The compatibility with elastomers, used in engines, is assured.

Specifications / Recommendations

ACEA A1-/B1-12 VW 508 00 / 509 00 VW TL 52577

Nominal Values

WHEELERS VOS SAE 0W-20	Unit	Value	Method
Density at 15°C	kg/m ³	836	DIN 51 757
Viscosity at 100°C	mm²/s	8,10	DIN 51 562
Viscosity at - 35°C (CCS)	mm²/s	3980	DIN 51 562
Pourpoint	°C	-35	DIN ISO 3016
Flashpoint	°C	234	DIN ISO 2592
TBN	mg KOH/g	8,0	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH Jubiläumsstraße 2 01139 Dresden / Germany Tel. 49 - (0) 351 16056831