

WHEELERS FOUKE- 4T

SAE 10W-40

High Performance Multigrade Oil for Motorcycles

Product Description

Wheelers 4T SAE 10W40 is a high performance special engine oil for all motor cycles with air- and water-cooled 4-stroke engines of highest output. It is the ideal partner for all sportive motor-cyles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

Wheelers 4T SAE 10W40 offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- Outstanding motor cleanliness, especially at pistons and valves.
- · good cold-starting properties

Specification

API SN ACEA A3 JASO MA2

Typical Values

| Wheelers 4T SAE 10W40 | Unit | Value | Method |
|-----------------------|----------|-------|--------------|
| Density at 15 | kg/m³ | 863 | DIN 51 757 |
| Viscosity at 40°C | mm²/s | 97,5 | DIN 51 562 |
| Viscosity at 100°C | mm²/s | 14,4 | DIN 51 562 |
| Viscosity Index | | 161 | DIN ISO 2909 |
| CCS at -25°C | mPa.s | 5590 | DIN 51 377 |
| Pourpoint | °C | -36 | DIN ISO 3016 |
| Flash Point | °C | 232 | DIN ISO 2592 |
| TBN | mg KOH/g | 10,5 | DIN ISO 3771 |

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH Jubiläumsstraße 2 01139 Dresden / Germany Tel. 49 - (0) 351 16056831