

WHEELERS FOUKE- 4T

SAE 15W-40

High Performance Multigrade Oil for Motorcycles

Product Description

Wheeler's 4T SAE 15W40 is a high performance special engine oil for all motor cycles with air- and water-cooled 4-stroke engines of highest output. It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

Wheeler's 4T SAE 15W40 offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- Highest wear protection of all power transmission components in motor and gear.
- all-seasons use at temperate climate.

Specification

ACEA A3-04
API SL
JASO MA

Typical Values

Wheeler's 4T SAE 15W40	Unit	Value	Method
Density at 15	kg/m ³	866	DIN 51 757
Viscosity at 40°C	mm ² /s	123	DIN 51 562
Viscosity at 100°C	mm ² /s	17,5	DIN 51 562
Viscosity Index		157	DIN ISO 2909
CCS at -30°C	mPa.s	5670	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flash Point	°C	226	DIN ISO 2592
TBN	mg KOH/g	8,4	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheeler's GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831