

# WHEELERS ATF DX III H Red

## AUTOMATIC TRANSMISSION FLUID

### Description

**WHEELERS ATF DEXRON III H**-fluid is an Automatic Transmission Fluid, which is made from mineral base oils and products from the synthesis technology, in combination with a special additive package.

### Application

**WHEELERS ATF DEXRON III H** is used in automatic vehicle gears, servo steering's, fluid couplings and hydrodynamic converters as well as in hydraulics of passenger cars, commercial vehicles, busses and construction vehicles, if an ATF of Dexron III H - type is recommended.

### Properties

**WHEELERS ATF DEXRON III H** affords following benefits:

- Optimally balanced frictional behaviour
- Very good wear protection
- Excellent cold fluidity
- Outstanding oxidation stability
- Good corrosion- and rust preventive properties
- Low foaming tendency and best elastomer compatibility

### Specification

DEXRON III H MB 229.3  
Allison C-4  
MB 236.1 & 236.5  
MAN 339 type Z-1 & V-1  
Volvo 97341

Mercon  
Voith 55.6335.30  
ZF TE-ML 02F, 03D, 04D, 09,11B, 14A, 17C  
Cat TO-2

### Nominal Values

WHEELERS ATF DEXRON III H	Unit	Value	Method
Density at 15	kg/m <sup>3</sup>	854	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	35,00	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	7,30	DIN 51 562
Viscosity Index		180	DIN ISO 2909
Pourpoint	°C	-48	DIN ISO 3016
Flash Point	°C	210	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

**Wheelers GmbH**  
Jubiläumsstraße 2  
01139 Dresden / Germany  
Tel. 49 - (0) 351 16056831