



# WHEELERS ATF DX VI

## AUTOMATIC TRANSMISSION FLUID

### Description

**WHEELERS ATF DEXRON DX VI** -fluid is an Automatic Transmission Fluid which is made by multivehicle anti-shudder additive technology optimized for passenger car applications.

### Application

**WHEELERS ATF DEXRON DX VI** is used in an extensive range of European and Asian passenger car service fill applications, it also can be used in commercial vehicle applications and power steering.

### Properties

**WHEELERS ATF DEXRON DX VI** affords following benefits:

- Exceptional oxidation behaviour
- Anti-shudder durability
- Excellent cold fluidity
- Smoother shifts over a long period of time
- Excellent anti-rust properties
- Low foaming tendency
- Good sludge and vanish control

### Specifications / Recommendations

- Allison C-4
- Allison TES-389
- Ford Mercon® -V
- Ford FNR5
- GM Dexron®-IID
- GM Dexron®-IIIG
- GM Dexron®-IIIH
- GM Dexron®-VI (does not meet viscosity profile)
- JASO 1-A
- MAN 339F
- MAN 339 Type V-1 / V-2
- MAN 339 Type Z-1 / Z-2

# WHEELERS ATF DX VI

- MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10 (NAG 1 / Shell 3403) 236.11, 236.81
- Shell 1375.4
- Voith H55.6335.xx / H55.6336.xx
- MOPAR AS68RC
- Texaco N402 (JATCO), ETL-7045E (BMW 7045E), ETL-8072B (BMW 5 Series)
- Volvo 97340 / 97341
- ZF TE-ML 03D, 04D, 05L, 09, 11, 14A, 14B, 16L, 17C, 20B, 21L
- **European/North America Specifications:** Audi G 055 025 / Audi G 052 162 / Audi G 052 990, BMW LA2634 / BMW LT 71141 / BMW 5 Series / BMW 7045E (3 Series), Chrysler ATF +3/+4, PSA AL-4, Renault DP-0, Volvo 4 Speed (P/N 1161621) Volvo P/N 1161540/1161640, VW G 052 162 / VW G 052 990 / VW G 055 025.
- **Asian Specifications:** Honda ATF Z-1, Hyundai/KIA SP-II / SP-III / JWS 3314 / 3317, JWS 3309 (Aisin Warner), Idemitsu K17 (JATCO), KIA Red-1, Mazda F-1 / ATF-M III / ATF-MV, Nissan 402 / Matic D/J/K, N402, Subaru ATF / ATF-HP, Toyota T / T-II / T-III / T-IV, Suzuki 3314 / 3317, Mitsubishi Diaqueen ATF J3 / SP-II / SP-III

## Typical Values

WHEELERS ATF DEXRON DX VI	Unit	Value	Method
Density at 15	kg/m <sup>3</sup>	850	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	34,30	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	7,20	DIN 51 562
Pourpoint	°C	48	DIN ISO 3016
Flash Point	°C	200	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

**Wheelers GmbH**  
Jubiläumsstraße 2  
01139 Dresden / Germany  
Tel. 49 - (0) 351 16056831