



WHEELERS ATF DSG

High Performance ATF for Double Clutch Transmission.

Description

WHEELERS ATF DSG is a high-performance automatic transmission fluid, which was developed for the latest generation of Double Clutch Transmission.

Application

WHEELERS ATF DSG is recommended for Audi- and VW-Double Clutch Transmission (DSG), that the ATF oil with No. TL 521 82 and TL 525 29 needs.

Properties

WHEELERS ATF DSG provides.

- extremely high wear resistance
- high thermal stability
- excellent viscosity-temperature behavior
- low pour point
- foamless, even under difficult conditions
- high oxidation stability
- high load-carrying capacity
- optimum friction characteristics
- Neutral to metals and sealing materials

Specification

Audi / Volkswagen / Seat / Skoda - G 052 182 A2/A6 (TL 52 182), G 052 529 A2/A6 (TL 52 529)
G 055 529 (TL 52 529-C),

BMW - DCTF-1 (83 220 440 214), DCTF-1+, DCTF-2, BMW 6-Speed DCT, MTF-LT-5 (83 22 2167 666), 83 22 2147 477, 83 22 2 148 578, 83 22 2 148 579 und 83 22 2 446 673

Borg Warner

BYD DCTs, Q/Byd-A1909.0058-2013

Bugatti Veyron

Citroen / Peugeot- 6DCT451 (PSA 9734.S2), Changan DCTF, Chrysler Powershift 6-Speed (Getrag), 68044345 EA & GA, Eaton PS-278, Ferrari 7-Speed (Getrag),- TF DCT-F3, Fiat 9.55550-MZ6, Ford WSS-M2C200-D2/ XT-11-QDC, Ford/Nissan Powershift 6-Speed (GFT)

Ford - WSS-M2C-936-A, part # 1490763/1490761, Fords WSS-M2C218-1A, -F-DC, part # KU7J M2C218AA, Geely 7 Speed

Mercedes Benz - MB 236.25, MB 236.21, MB 236.22, MB 236.24 und MB 239.21

Mitsubishi - TC-SST 6-Speed (GFT), MZ320065 DiaQueen SSTF-1, DCT Transmission oil for ZF, Peugeot/Citroen DCS 6-Speed, 9734.S2, Porsche - 043 207 29, 043 207 30, 000 043 20, 000 043 305 13, 999 917 080 01, Porsche - 000 043 210 44, 971 094 307 02A, Renault 77 11 785 243 (DW5), Renault EDC 6-Speed (Getrag), EDC 7, Renault - BOT 450, Volvo Powershift 6-Speed

(GFT)/1161838/1161839,

VW G 052 536, 055 536, VW Audi G 052 512, VW (Audi, Seat, Skoda) 6-Speed, VW/Audi TL 52529 / G 052 529 A2 or A6 (fluid) / DSG 7= S-tronic 7/ 7-Speed VW (Audi, Seat, Skoda), VW/Audi G 055 529, VW/Audi TL 521 82 / G 052 182 A2 or A6(fluid), ZF TE-ML 11 (ZF004743), ZF Lifeguard Fluid 8.2

Nominal Values

| WHEELERS ATF DSG | Unit | Value | Method |
|----------------------------|--------------------|--------------|---------------|
| Density at 15 | kg/m ³ | 848 | DIN 51 757 |
| Viscosity at 40°C | mm ² /s | 38 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 7,6 | DIN 51 562 |
| Viscosity Index | | 172 | DIN ISO 2909 |
| Dynamic Viscosity at -40°C | mPa.s | < 18.000 | DIN 51 938 |
| Pourpoint | °C | -45 | DIN ISO 3016 |
| Flash Point | °C | > 200 | DIN ISO 2592 |

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831