



WHEELERS UNITRACTOL TOU

SAE 80W-85W

SUPER UNIVERSAL TRACTOR OIL

Description

Wheeler's UNITRACTOL TOU SAE 80W-85W is made on the base of highly refined base oils. By the addition with selected active components the product protects the materials in its effective range outstandingly against wear and corrosion, while the protection against aging cares for a clear improvement of the oxidation stability, whereby extended oil drain intervals are possible. The friction behaviour is aligned to the requirements of many materials of wet breaks. A shear-stable VI-improver provides the multigrade performance of the oil, whereby the All-seasons use is granted.

Application

Wheeler's UNITRACTOL TOU SAE 80W-85W is used in tractors and forestry or construction machineries and in all kinds of agricultural devices for the universal provision of gears, hydraulics and wet breaks. It has to be applied according constructors manual, if a TUO (Tractor Universal Oil) resp. an UTTO (Universal Tractor Transmission Oil) is recommended for the provision of the equipment assembly.

Specification

API GL-4	ZF TE-ML-03E / -06
Ford M2C 134D, M2C 86A-C	John Deere J-20C u. D
Case MS-1204, -1205, -1206, -1207, -1209, -1210	Allison C-4 & C-3
Caterpillar TO-2	Deutz Hydr Trans Fluid
Massey Ferguson M 1143, 1145	

Typical Properties

Wheeler's UNITRACTOL TOU SAE 80W-85W	Unit	Value	Method
Density at 15°C	kg/m ³	871	DIN 51 757
Viscosity at 40°C	mm ² /s	65,12	DIN 51 562
Viscosity at 100°C	mm ² /s	10,94	DIN 51 562
Viscosity Index		160	DIN ISO 2909
dynam. viscos.at -25°C	mPa.s	6320	ASTM D5293
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	226	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheeler's GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831