



WHEELERS MOTOR OIL- WXV

SAE 5W-30

Fully Synthetic High-Performance Motor Oil for Cars with Exhaust Aftertreatment and without

Description

Wheelers Motor oil WXV SAE 5W-30 is a high-performance fuel economy oil made from synthetic base oils. It has been developed for the use in passenger cars gasoline- and diesel-engines of modern technology, also for diesel engines with pump / nozzle injection system (PD), thus also an ideal solution for light commercial vehicles.

Due to its progressive conception it provides an extremely wide range of performances:

- Low sulphur-, phosphorus- and ash-content reduce poisoning of catalysators in gasoline engines and decrease the built-up of particles in the diesel particulate filter (DPF) and assist thus the environmental protection by lower pollution.
- Novel high-performance additives assure optimal wear protection and best motor cleanliness.
- Excellent thermal oxidation stability reduces oil aging and allows longer drain intervals at maximum motor protection.
- Best low temperature properties enable unproblematic cold-start of the motor and contribute decisively to a longer operating life of the engine by rapid oil circulation.

Specification/Recommendation

ACEA C3 / C2-12

API SN

MB 229.52 / 229.51 / 229.31

BMW Longlife-04

VW 505 01 / 502 00 / 505 00

GM dexos 2

Nominal Values

Wheelers WXV SAE 5W-30	Unit	Value	Method
Density at 15°C	kg/m ³	853	DIN 51 757
Viscosity at 40°C	mm ² /s	70,3	DIN 51 562
Viscosity at 100°C	mm ² /s	11,90	DIN 51 562
Viscosity Index		167	DIN ISO 2909
CCS at -35°C	mPa.s	5770	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	234	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831