



WHEELERS MOTOR OIL- GF

SAE 5W-20

Fully Synthetic Fuel-Efficient Engine Oil.

Product Description

WHEELERS GF SAE 5W-20 is a high-performance lubricant, which especially is designed for the most advanced gasoline and diesel engines of passenger cars, which are operated with low viscosity fuel saving engine oils. It is suitable for use in all types of modern vehicles where this viscosity grade is recommended. This includes high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines found in passenger cars and light vans.

WHEELERS GF SAE 5W-20 is designed on base of synthetic oils only. It persuades by an excellent lubricity and shows outstanding properties and benefits :

- stable lubrication film at all operation conditions.
- outstanding cold starting properties even at low temperatures
- long motor life by complex wear protection and cleanliness from cylinder head down to oil sump.
- low oil consumption and high fuel efficiency.
- lower environmental impact by reduced exhaust gas emissions and long oil drain intervals

Specifications / Recommendations

API SP	Toyota	Chrysler MS-6395
ILSAC GF-6A	Nissan	Ford WSS-M2C945-A
GM Dexos1 Gen 3	Lexus	Ford WSS-M2C945-B1
Isuzu, Suzuki	Kia	Ford WSS-M2C930-A
Honda	Subaru	Ford WSS-M2C960-A
GM 6094M	Mazda, Daihatsu	

Nominal Values

WHEELERS GF SAE 5W-20	Unit	Value	Method
Density at 15°C	kg/m ³	852	DIN 51 757
Density at 40°C	mm ² /s	47,5	DIN 51 562
Viscosity at 100°C	mm ² /s	8,50	DIN 51 562
Viscosity index		157	DIN ISO 2909
CCS at -30°C	mPa.s	4750	ASTM D5293
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	8,1	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheeler's GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831