

WHEELERS MOTOR OIL -BM

SAE 5W-40

Performance Low Friction Oil

Description

Wheeler's BM SAE 5W-40 is a high-performance low friction oil, which is designed for gasoline and diesel engines of passenger cars, and which especially can be used for fuel injected and turbo charged engines.

It is blended from high quality hydrocracked base oils and selected additives. This makes for a lubricant quality which fulfils and exceeds all requirements of modern passenger car engines.

Product Benefits

Wheeler's BM SAE 5W-40 has following advantages to be pointed out

- excellent cold start and fast oil feed even at temperatures down to lower than -30°C reduce fuel consumption.
- optimized high temperature viscosity and outstanding low friction properties lower oil-caused emissions.
- high wear and corrosion protection and a very good dispersancy provide for an excellent cleanliness of the engine and for long motor life.
- All seasons use by outstanding temperature-viscosity properties and reliable performance reserves even at long drain intervals.

Specification / Recommendation

ACEA A3-/ B4

API SN / CF

VW 502 00 / 505 00

PSA B71 2296

Renault RN0700 und RN0710

Opel GM-LL-B-025

MB 226.5, MB 229.5

Porsche A 40

BMW Longlife-01

Lamborghini

Maserati

Typical Properties

Wheeler's BM SAE 5W-40	Unit	Value	Method
Density at 15	kg/m ³	856	DIN 51 757
Viscosity at 100°C		14,3	DIN 51 562
Viscosity Index	mPa.s	170	DIN ISO 2909
CCS at -30°C	°C	6010	DIN 51 377
Pourpoint	mPa.s	-36	DIN ISO 3016
Flash Point	°C	224	DIN ISO 2592
TBN	mg KOH/g	10,4	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information's to be available by MSDS.

Wheeler's GmbH
 Jubiläumsstraße 2
 01139 Dresden / Germany
 Tel. 49 - (0) 351 16056831